

Stainless Panel Builder Gauges

Applications

- Fits industry standard 2.56" panel hole cutout
- Suitable for corrosive environments
- Used in gaseous and liquid media

Feature

- ASME B40.100 Grade A \pm 2-1-2% full scale accuracy

Materials

- Wetted parts: 316L stainless steel
- Case and ring: 304 stainless steel
- Stop pin: white aluminum with black lettering
- Pointer: black aluminum
- Case: glycerin filled
- Window lens: laminated safety glass

Specifications

- Ambient temperature range: -4°F to 140°F (-20°C to 60°C)
- Maximum media temperature 212°F maximum

PSI Range	Figure Interval	Minor Gradient	2-1/2" Face 1/4" Lower Back Mount Part #
0-15	3	.2	PBLSS15
0-30	5	.5	PBLSS30
0-60	10	1	PBLSS60
0-100	20	2	PBLSS100
0-160	20	2	PBLSS160
0-200	50	5	PBLSS200
0-300	50	5	PBLSS300
0-400	100	10	PBLSS400
0-600	100	10	PBLSS600
0-800	200	20	PBLSS800
0-1000	200	20	PBLSS1000
0-1500	300	20	PBLSS1500
0-2000	500	50	PBLSS2000
0-3000	500	50	PBLSS3000
0-5000	1000	100	PBLSS5000



Contractor Pressure Gauges

Feature

- Accuracy class: \pm 1% of span

Materials

- Wetted parts: copper alloy
- Window: acrylic, snap in
- Dial: aluminum, white
- Pointer: aluminum, black, adjustable
- Mounting flanged/bracket, rear flange: stainless steel
- Case: stainless steel

Specification

- Temperature range: -40°F to 250°F (-40°C to 120°C)

PSI Range	4-1/2" face, 1/4" Lower Mount Part #
0-15	4277750-0001
0-30	4277768-0001
0-60	4277776-0003

